Båndsling / Webslings

Sikkerhedsfaktor: 7:1
Båndsling med farvekode som angiver WLL-tons, samt label m. data
Vi kan tilbyde båndsling som standard op til WLL 5,0 og omkreds på 4,0 meter
Ønskes andre længder og størrelser kan dette skaffes
Fremstillet af polyester iflg. EN-standard EN 1492-1
Båndsling bruges til forskellige løfteopgaver. Speciel velegnet til løft af byrder uden skarpe kanter og produkter der ikke må ridses, af f.eks. en wirestrop eller kæde

Safety factor: 7:1
Websling with color which indicate the WLL and label with data
We can offer webslings as standard up to WLL 5,0 and length of 4,0 meters
Other length and sizes on request
Made of polyester - EN 1492-1
Especially suitable for lifting loads with no sharp edges and products must not be scratched, for example a wire strap or chain

Length effektive mtr.	Length circular mtr.	WLL 0,5 tons	WLL 1,0 tons	WLL 2,0 tons	WLL 3,0 tons	WLL 5,0 tons
1,0	2,0	BSL00510	BSL01010	BSL02010	BSL03010	BSL05010
2,0	4,0	BSL00520	BSL01020	BSL02020	BSL03020	BSL05020
3,0	6,0	BSL00530	BSL01030	BSL02030	BSL03030	BSL05030
4,0	8,0	BSL00540	BSL01040	BSL02040	BSL03040	BSL05040

Rundsling, sort / Roundslings, Black

Til scenebrug iflg. BGV C1
100% polyester fibre
Skånsom overfor sårbare overflader
WLL angivet på belastningsskilt
Sikkerhedsfaktor: 7:1
Andre længder på forespørgsel

For stage use acc. BGV C1
100% polyester fiber
Gentle against vulnerable surfaces
WLL indicated on the load sign
Safety factor: 7:1
Other lengths on request

Art No.	Effective length m	Circular length m	WLL tons
SRS02005	0,5	1,0	2,0
SRS02010	1,0	2,0	2,0
SRS02015	1,5	3,0	2,0
SRS02020	2,0	4,0	2,0

Rundsling, sort / Roundslings, Black
Type: Wire galv.

Til scenebrug iflg. BGV C1
Iflg. EN 1492-2 og EN 13414-2
Sikkerhedsfaktor: 5:1
Min. radius 6 mm
Varme bestandig op til +175 grader C
Label for nem identifikation
Andre længder på forespørgsel

For stage use acc. BGV C1
According to. EN 1492-2 and EN 13414-2
Safety factor: 5:1
Min. radius 6 mm
Heat resistant up to +175 ° C
Label for easy identification
Other lengths on request

Art No.	Type	Effective length m	Circular length mm	WLL tons
SRW02005	Wire	0,5	1,0	2,0
SRW02010	Wire	1,0	2,0	2,0
SRW02015	Wire	1,5	3,0	2,0
SRW02020	Wire	2,0	4,0	2,0
SRW02030	Wire	3,0	6,0	2,0

For alle produkter: Vægt, størrelse og farve kan variere

+45 4619 1565 - info@scanlifting.dk