



Med sammenfoldeligt stativ/ben  
Leveres med:  
Løbekat med parkeringsbremse  
Integreret horizontal justering  
Montering for bom

With collapsible lateral stands  
Delivered with:  
Park-brake trolley  
Integrated horizontal adjuster  
Beam mountings

### Alu portalkran, lille / Alu Gantry Crane, Small

Art No.	Payload Kg	Beam length mm		Total height mm		Lower edge alu beam mm		Adjustment range mm		Lateral stand mm		Weight Kg
		Clear width	Total	Min.	Max.	Min.	Max.	Beam support	Adjustment foot	Width	Height	
S1311040	1000	4000	4100	1640	2740	1350	2450	700	400	1300	1160	91
S1311050	1000	5000	5100	1640	2740	1350	2450	700	400	1300	1160	103
S1311060	1000	6000	6100	1640	2740	1330	2430	700	400	1300	1160	117
S1311070	1000	7000	7100	1640	2740	1330	2430	700	400	1300	1160	126
S1311080	1000	8000	8100	1640	2740	1330	2430	700	400	1300	1160	167
S1311540	1500	4000	4100	1640	2740	1330	2430	700	400	1300	1160	99
S1311550	1500	5000	5100	1640	2740	1330	2430	700	400	1300	1160	128
S1311560	1500	6000	6100	1640	2740	1330	2430	700	400	1300	1160	141

### Alu portalkran, mellem / Alu Gantry Crane, Medium

Art No.	Payload Kg	Beam length mm		Total height mm		Lower edge alu beam mm		Adjustment range mm		Lateral stand mm		Weight Kg
		Clear width	Total	Min.	Max.	Min.	Max.	Beam support	Adjustment foot	Width	Height	
S1321040	1000	4000	4100	2120	3370	1830	3080	850	400	1740	1540	97
S1321050	1000	5000	5100	2120	3370	1830	3080	850	400	1740	1540	109
S1321060	1000	6000	6100	2120	3370	1830	3060	850	400	1740	1540	123
S1321070	1000	7000	7100	2120	3370	1830	3060	850	400	1740	1540	132
S1321080	1000	8000	8100	2120	3370	1830	3060	850	400	1740	1540	173
S1321540	1500	4000	4100	2120	3370	1830	3060	850	400	1740	1540	105
S1321550	1500	5000	5100	2120	3370	1830	3060	850	400	1740	1540	134
S1321560	1500	6000	6100	2120	3370	1830	3060	850	400	1740	1540	147

### Alu portalkran, stor / Alu Gantry Crane, Large

Art No.	Payload Kg	Beam length mm		Total height mm		Lower edge alu beam mm		Adjustment range mm		Lateral stand mm		Weight Kg
		Clear width	Total	Min.	Max.	Min.	Max.	Beam support	Adjustment foot	Width	Height	
S1331040	1000	4000	4100	2700	4400	2410	4110	1300	400	2240	1970	149
S1331050	1000	5000	5100	2700	4400	2410	4110	1300	400	2240	1970	161
S1331060	1000	6000	6100	2700	4400	2390	4090	1300	400	2240	1970	175
S1331070	1000	7000	7100	2700	4400	2390	4090	1300	400	2240	1970	184
S1331080	1000	8000	8100	2700	4400	2390	4090	1300	400	2240	1970	225
S1331540	1500	4000	4100	2700	4400	2390	4090	1300	400	2240	1970	157
S1331550	1500	5000	5100	2700	4400	2390	4090	1300	400	2240	1970	186
S1331560	1500	6000	6100	2700	4400	2390	4090	1300	400	2240	1970	199

For all products: Weight, size and color may vary