

Flytbar under belastning  
Med sammenfødeligt stativ/ben  
Leveres med:  
Løbekat med parkeringsbremse  
Integreret horizontal justering  
Montering for bom

Moveable under load  
With collapsible lateral stands  
Delivered with:  
Top-mounted park-brake trolley  
Integrated horizontal adjuster  
Beam mountings

## Alu portalkran, dobbelt bom m. hjul, lille Alu Gantry Crane, Double Beam with Wheels, Small

Art No.	Payload kg	Beam length mm		Total height mm		Lower edge alu double beam mm		Adjustment range mm	Lateral stand mm		Weight Kg
		Clear width	Total	Min.	Max.	Min.	Max.	Beam support	Width	Height	
S14401040	1000	4000	4100	2150	2550	1820	2220	400	1490	1430	234
S14401050	1000	5000	5100	2150	2550	1820	2220	400	1490	1430	258
S14401060	1000	6000	6100	2150	2550	1800	2200	400	1490	1430	286
S14401070	1000	7000	7100	2150	2550	1800	2200	400	1490	1430	304
S14401540	1500	4000	4100	2150	2550	1820	2220	400	1490	1430	234
S14401550	1500	5000	5100	2150	2550	1820	2220	400	1490	1430	258
S14401560	1500	6000	6100	2150	2550	1800	2200	400	1490	1430	286
S14401570	1500	7000	7100	2150	2550	1800	2200	400	1490	1430	304

## Alu portalkran, dobbelt bom m. hjul, mellem Alu Gantry Crane, Double Beam with Wheels, Medium

Art No.	Payload Kg	Beam length mm		Total height mm		Lower edge alu double beam mm		Adjustment range mm	Lateral stand mm		Weight Kg
		Clear width	Total	Min.	Max.	Min.	Max.	Beam support	Width	Height	
S14501040	1000	4000	4100	2590	3440	2260	3110	850	2000	1870	260
S14501050	1000	5000	5100	2590	3440	2260	3110	850	2000	1870	284
S14501060	1000	6000	6100	2590	3440	2240	3090	850	2000	1870	312
S14501070	1000	7000	7100	2590	3440	2240	3090	850	2000	1870	330
S14501540	1500	4000	4100	2590	3440	2260	3110	850	2000	1870	260
S14501550	1500	5000	5100	2590	3440	2260	3110	850	2000	1870	284
S14501560	1500	6000	6100	2590	3440	2240	3090	850	2000	1870	312
S14501570	1500	7000	7100	2590	3440	2240	3090	850	2000	1870	330

## Alu portalkran, dobbelt bom m. hjul, stor Alu Gantry Crane, Double Beam with Wheels, Large

Art No.	Payload Kg	Beam length mm		Total height mm		Lower edge alu double beam mm		Adjustment range mm	Lateral stand mm		Weight Kg
		Clear width	Total	Min.	Max.	Min.	Max.	Beam support	Width	Height	
S14601040	1000	4000	4100	2920	4220	2590	3890	1300	2320	2130	278
S14601050	1000	5000	5100	2920	4220	2590	3890	1300	2320	2130	302
S14601060	1000	6000	6100	2920	4220	2570	3870	1300	2320	2130	330
S14601070	1000	7000	7100	2920	4220	2570	3870	1300	2320	2130	348
S14601540	1500	4000	4100	2920	4220	2590	3890	1300	2320	2130	278
S14601550	1500	5000	5100	2920	4220	2590	3890	1300	2320	2130	302
S14601560	1500	6000	6100	2920	4220	2570	3870	1300	2320	2130	330
S14601570	1500	7000	7100	2920	4220	2570	3870	1300	2320	2130	348

For all products: Weight, size and color may vary