


Stålwire galvaniseret / Wire Rope Galvanized

4X3 FC




Med fiberkerne
With fibercore

Art No.	Dia mm	Min breaking strength 160-180 kp/mm ²	Weight Kg/%
G43F010	1,0	67	0,99

Stålwire rustfri / Wire Rope Stainless Steel

DIN 3053 1x19

AISI 316



Med stålkerner
With steelcore

Art No.	Dia mm	Min breaking strength 160-180 kp/mm ²	Weight Kg/%
A4119010	1,0	84	0,99
A4119012	1,25	165	1,10
A4119015	1,5	189	1,20
A4119020	2,0	340	2,00
A4119025	2,5	550	3,10
A4119030	3,0	750	4,50
A4119040	4,0	1400	7,90
A4119050	5,0	2100	12,40
A4119060	6,0	3000	17,80
A4119070	7,0	4100	24,30
A4119080	8,0	5400	31,70
A4119100	10,0	6900	49,40
A4119120	12,0	8600	74,30

Stålwire rustfri / Wire Rope Stainless Steel

7x7 PVC white

AISI 316




Med stålkerner
With steelcore

Art No.	Dia mm	Min breaking strength 160-180 kp/mm ²	Weight Kg/%
R77P35	3-5	500	5,20
R77P46	4-6	1208	9,00
R77P48	4-8	1208	11,00
R77P57	5-7	1438	12,00
R77P58	5-8	1438	15,00

Stålwire rustfri / Wire Rope Stainless Steel

1x19 PVC white

AISI 316



Med stålkerner
With steelcore

Art No.	Dia mm	Min breaking strength 160-180 kp/mm ²	Weight Kg/%
R119P46	4-5	1400	11,20
R119P48	4-8	1400	11,50
R119P58	5-8	2100	16,00

For all products: Weight, size and color may vary