

Grade 80 H-sjækel / H-Shackle



Sjækler godkendt til løft
Sikkerhedsfaktor 4:1

Shackles approved for lifting
Safety factor 4:1

Art No.	Max. load tons	For chain mm	Bolt dia mm	Opening mm	Weight Kg
801408	2,0	7/8	10	15	0,11
801410	3,2	10	12	21	0,22
801413	5,4	13	16	25	0,38
801416	8,0	16	20	30	0,73
801418	10,5	18/19	22	-	-
801420	12,5	20	25	-	-
801422	15,5	22	28	-	-
801424	19,0	24	30	-	-
801426	23,0	26	32	-	-
801430	32,0	30	38	-	-
801433	40,0	32/33	42	-	-

Grade 80 D-sjækel / D-Shackle



Sjækler godkendt til løft
Sikkerhedsfaktor 4:1

Shackles approved for lifting
Safety factor 4:1

Art No.	Max. load tons	For chain mm	Bolt dia mm	Opening mm	Weight Kg
801308	2,0	7/8	10	15	0,11
801310	3,2	10	12	21	0,22
801313	5,4	13	16	25	0,38
801316	8,0	16	20	30	0,73
801318	10,5	18/19	22	-	-
801320	12,5	20	25	-	-
801322	15,5	22	28	-	-
801324	19,0	24	30	-	-
801326	23,0	26	32	-	-
801330	32,0	30	38	-	-
801333	40,0	32/33	42	-	-

Kran sjækel / Crane Shackle



Anvendes for det meste til krankroge på
hydrauliske kraner, hvor andre sjækler ikke kan anvendes

Typically used for crane hooks on hydraulic
cranes, where other shackles can't be used


Art No.	Capacity tons	Inner height mm	Opening mm	Bolt dia mm	Weight Kg
KS100	10,0	77	70	30	3,9

H-sjækel, galvaniseret / H-Shackle, Galvanized



Galvaniseret
Handels sjækel,
ikke godkendt til løft

Galvanized
Commercial shackle,
not approved for lifting



Art No.	WLL tons	Size inches	Size mm	A mm	H mm	Weight Kg
EG826005	0,08	3/16	5	10	20	0,02
EG826006	0,10	1/4	6	12	24	0,03
EG826008	0,20	5/16	8	16	32	0,07
EG826010	0,30	3/8	10	20	40	0,12
EG826011	0,40	7/16	11	22	44	0,17
EG826012	0,50	1/2	12	24	48	0,21
EG826014	0,50	9/16	14	28	56	0,35
EG826016	0,80	5/8	16	32	64	0,50
EG826020	1,10	3/4	20	38	74	0,94
EG826022	1,50	7/8	22	44	88	1,34
EG826024	2,00	1	24	48	96	1,98
EG826028	3,00	1 1/8	28	56	112	2,70
EG826032	3,50	1 1/4	32	64	128	4,33
EG826038	5,00	1 1/2	38	76	152	6,07