

Manuel stabler / Manual Stacker



PM120

PM120

Stabler med håndsving har lav egenvægt i forhold til dens løfteevne
Udstyret med justerbar gaffel for løft af forskellig størrelse paller
Store gummi baghjul og i front er små drejelige PU hjul
Manuel bremse

PM120

The winch stacker has a low weight compared to the rated lift capacity
Equipped with adjustable forks for half size pallets
large sized rubber rear wheels and small front PU castor wheels
Manual brake

M100 - M200

Manuelt betjent, med håndspil og stålwire som giver et præcist og hurtigt løft / sænkings funktion
Automatisk bremse system sikrer sikker betjening
4 drejelige hjul

M100 - M200

Operated by a manual hand winch and a steel wire which gives an accurate and fast lift / lowering function
Automatic brake system ensures a safe lowering
4 castor wheels



M100 - M200

Art No.	Type	Capacity kg	Lift height min - max	Platform size mm	Fork (LxWxT) mm	Steer/load wheel mm	Dimensions (LxWxH) mm	Weight Kg
PM120	Manual	120	95 - 1050	-	450x(345 - 485)x14	200x50 / 50x20	720x485x1360	31
M100	Manual	100	130 - 1500	480x600	400x330x40	125x35 / 75x20	840x600x1830	48
M200	Manual	200	130 - 1500	480x600	400x330x40	125x35 / 75x20	840x600x1920	70

Stabler / Stacker



Hydraulisk stabler, kan håndtere 1/2 paller, men kan også monteres med en plade så de kan bruges som mobilt løftebord
Den foldbare fodpumpe bruges til løft, og håndtag til sænkning
Fås også som elektrisk stabler
Indbygget overbelastningsventil, vedligeholdelsesfrie bøsninger og lejer
Lukket hydraulisk system
Baghjul er drejelige og monteret med bremse
Styrehjul: 125x35 mm
Lastehjul: 75x20 mm

The hydraulic stacker is equipped with both fixed and hardchromed platform for multipurpose handling
You can handle half sized pallets and/or use it as a mobile lifting table
Manual stacker with foldable foot pump lever for lifting and manual knob for lowering
Electric stacker with battery for more ergonomic operation
Built in overload valve for overload protection, maintenance-free bushings and bearings
Closed hydraulic system with protected / sealed pump
Rear castor wheels with foot brake
Steering wheel: 125x35 mm
Load wheel: 75x20 mm



Art No.	Lift motor W	Battery Ah / V
ST400-1500EL	700	74 / 12

Art No.	Type	Capacity kg	Lift height min - max	Platform size mm	Fork length mm	Width between forks mm	Dimensions (LxWxH) mm	Weight Kg
ST400-850	Footpump	400	85 - 850	650 x 580	650	350	1050 x 580 x 1060	75
ST400-1100	Footpump	400	80 - 1100	650 x 580	650	350	1050 x 580 x 1300	98
ST400-1500	Footpump	400	80 - 1500	650 x 580	650	350	1050 x 580 x 1620	110
ST400-1500EL	Electric	400	80 - 1500	650 x 580	650	350	1100 x 580 x 1620	145

For all products: Weight, size and color may vary